

Display/Operation

Buzzer function	no
Colors, number	7
Dimmable	yes
Function indicator	Runlight Mode Level Mode Segment Mode Color circle mode
IO-Link communication indicator	Green LED
Module supply indicator	Green LED
Predefined colors	Yellow white Green Blue Red Orange configurable
Segments, number max.	6
Setting	Function indicator

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Operating voltage U_b	18...30.2 VDC
Rated operating voltage U_e DC	24 V

Environmental conditions

Ambient temperature	-5...55 °C
IP rating	IP65
Storage temperature	-25...70 °C

Functional safety

MTTF (40 °C)	146.5 a
---------------------	---------

General data

Approval/Conformity	CE cULus WEEE
Life expectancy min.	50000 h
Scope of delivery	Device Nut Rubber gasket Washer User manual

Material

Housing material	PC, Transparent PPS
-------------------------	------------------------

Mechanical data

Dimension	61.8 x 62.4 x 57.5 mm
Mounting	Screws M22

Output/Interface

Additional function	Daisy chain (2x devices per IO-Link port)
Cycle time min.	8.4 ms
Frame type	2.V
IO-Link function	Device
IO-Link version	1.1
Interface	IO-Link 1.1
Process data IN	2 bytes
Process data OUT	8 bytes
Process data cycle min.	8.4 ms


Remarks

See short guide

For further information about the MTTF and B10d see MTTF / B10d certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



IO-Link interface

PIN 1: +24V

PIN 2: Comm. (Exp. Mode)

PIN 3: GND, reference potential

PIN 4: C/Q, IO-Link DC-Channel