

Basic features

| | |
|----------------------------|-------------------|
| Application | Welding area |
| Approval/Conformity | CE EAC WEEE |

Environmental conditions

| | |
|--|--------------|
| Cable temperature, fixed routing | -50...130 °C |
| Cable temperature, flexible routing | -40...125 °C |
| IP rating | IP65/IP65 |

Electrical connection

| | |
|--|---|
| Bending radius min., fixed cable | 8 x D |
| Bending radius min., flexible cable | 15 x D |
| Cable | TPE welding spark resistant gray, 1.00 m |
| Cable diameter D | 4.40 mm ±0.20 mm |
| Conductor cross-section | 0.34 mm ² |
| Connection 1 | M8x1-Female, straight, 3-pin, A- coded |
| Connection 2 | M8x1-Male, straight, 3-pin, A- coded |
| Number of conductors | 3 |
| System | Molded/Molded |

Material

| | |
|------------------------------------|---|
| Cable jacket material, note | welding spark resistant |
| Cable jacket, material | TPE |
| Material contact carrier | PUR, special/PUR, special |
| Material contacts | Bronze/Brass |
| Material cover nut | Brass PTFE coated/Brass PTFE coated |
| Material grip | PUR, special/PUR, special |

Mechanical data

| | |
|----------------------------------|---------------|
| Cable jacket, color | gray |
| Cable length L | 1.00 m |
| Tightening torque pigtail | 0.4 Nm/0.4 Nm |


Electrical data

| | |
|--|-----------------|
| Operating voltage U_b | 60 VDC / 60 VAC |
| Rated current (40 °C) | 4.0 A |

Remarks

Flame-retarding
 Maximum temperature at outer jacket from weld spatter/beads short-time 800°C.
 Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

Connector Drawings



II
PIN 1: brown
PIN 3: blue
PIN 4: black

I
PIN 1: brown
PIN 3: blue
PIN 4: black

Wiring Diagrams

