

Basic features

Approval/Conformity	CE cULus EAC WEEE
Scope of delivery	User manual
Style	tubular

Display/Operation

IO-Link communication indicator	Green LED
Module supply indicator	Green LED
Sensor supply US indicator	Green LED

Electrical connection

Connection (COM 1)	M12x1-Male, 4-pin, A-coded
Connection slots	M12x1-Female, 8-pin, A-coded
Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm

Electrical data

Burst	4A
Configurable inputs/outputs	no
Current consumption without load, max.	65 mA
ESD	3A
IO-Link function	Device
IO-Link ports, number	1
Operating voltage U_b	18...30.2 VDC
Rated operating voltage U_e DC	24 V

Environmental conditions

Ambient temperature	-5...55 °C
Ambient temperature UL max.	45 °C
Protection degree	IP67 when threaded in
Storage temperature	-25...70 °C

Functional safety

MTTF (40 °C)	124.5 a
--------------	---------

Material

Gasket, material	FKM 75
Housing material	Stainless steel (1.4404)
	PTFE
Housing shield	yes

Mechanical data

Dimension	Ø 18 x 118 mm
Mounting	Diameter 18.0 mm Mounting clamps

Output/Interface

Auxiliary interfaces	RS232
Cycle time min.	35.2 ms
Digital inputs	4x PNP, Type 3
IO-Link version	1.1
Interface	IO-Link 1.1
Process data IN	32 bytes
Process data OUT	32 bytes
Process data cycle min.	35.2 ms
Transfer rate	COM2 (38.4 kBaud)


Remarks

See short guide

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings




IO-Link

PIN 1: +24V, 1.4A

PIN 2: n.c.

PIN 3: GND, reference potential

PIN 4: C/Q, IO-Link



PIN 1: TX

PIN2: RTS

PIN 3: RX

PIN4: CTS

PIN5: DIN1

PIN6: DIN2

PIN 7: +24V

PIN 8: GND