

4MT5  
(CYJV CABLE ASSEMBLY)



## Basic features

|                     |                            |
|---------------------|----------------------------|
| Approval/Conformity | CE<br>cULus<br>EAC<br>WEEE |
|---------------------|----------------------------|

## Electrical connection

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Bending radius min., fixed cable    | 5 x D                                 |
| Bending radius min., flexible cable | 10 x D                                |
| Cable                               | PUR black, 3 m, Drag chain compatible |
| Cable diameter D                    | 4.70 mm ±0.20 mm                      |
| Cable, bending cycles min.          | 5 million                             |
| Conductor cross-section             | 0.34 mm <sup>2</sup>                  |
| Connection                          | M8x1-Female, straight, 4-pin, A-coded |
| Connector configuration             | Straight                              |
| Number of conductors                | 4                                     |
| Number of pins                      | 4                                     |
| System                              | Molded                                |

## Electrical data

|                         |                 |
|-------------------------|-----------------|
| Operating voltage $U_b$ | 60 VDC / 60 VAC |
| Rated current (40 °C)   | 4.0 A           |

## Environmental conditions

|   |             |
|---|-------------|
| Cable temperature UL max., fixed routing    | 80 °C       |
| Cable temperature UL max., flexible routing | 80 °C       |
| Cable temperature, drag chain               | -25...60 °C |
| Cable temperature, fixed routing            | -50...90 °C |
| Cable temperature, flexible routing         | -25...90 °C |
| IP rating                                   | IP67, IP69K |

## Material

|                          |                                      |
|--------------------------|--------------------------------------|
| Cable jacket, material   | PUR                                  |
| Material contact carrier | PUR                                  |
| Material contacts        | Bronze                               |
| Material cover nut       | Die-cast zinc or nickel plated brass |
| Material grip            | PUR                                  |

## Mechanical data

|   |                       |
|---|-----------------------|
| Acceleration max., drag chain           | 5 m/s <sup>2</sup>    |
| Cable jacket, color                     | black                 |
| Cable length L                          | 3.00 m                |
| Cable properties                        | Drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m                   |
| Tightening torque pigtail               | 0.4 Nm                |
| Traverse speed max., drag chain         | 200 m/min             |
| Vertical travel permitted, drag chain   | 5 m                   |


## Output/Interface

|                  |               |
|------------------|---------------|
| Switching output | Complementary |
|------------------|---------------|

## Remarks

Cable construction acc. to UL-AWM Style 20549  
Halogen-free per DIN VDE 0472 Part 815  
Silicone-free  
Flame-retarding acc. to IEC 60332-2  
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

## Connector Drawings



PIN 1: brown  
PIN 2: white  
PIN 3: blue  
PIN 4: black

## Wiring Diagrams

